

**In the Claims**

The following Listing of Claims replaces all prior versions in the application:

LISTING OF CLAIMS

1. (Original) A method of operating a wireless communication system comprising:  
  
in a controller, receiving streaming data contention-window slot assignment requests from streaming transmitter units;  
  
in the controller, assigning contention-window slot numbers to the requesting streaming transmitter units;  
  
in the controller, sending an indication of available contention-window slots to other transmitter units; and  
  
in the other transmitter units, using a randomly selected contention-window slot to begin transmitting, wherein the randomly selected contention-window slot is selected from contention-window slots other than the assigned contention-window slots.
2. (Original) The method of claim 1, wherein the indication of the available contention-window slots is an indication of the first unassigned slot.
3. (Original) The method of claim 2 wherein the randomly selected slot is selected from slots greater or equal to the first unassigned slot.
4. (Original) The method of claim 1 wherein the streaming data is audio data.

5. (Original) The method of claim 1 wherein the streaming data is video data.
6. (Original) The method of claim 1 wherein the number of assigned contention-window slots is limited.
7. (Previously presented) A wireless communication system comprising:
  - a controller adapted to receive streaming data contention-window slot assignment requests from streaming transmitter units, the controller adapted to assign contention-window slot numbers to requesting streaming transmitter units and send an indication of available contention-window slots to other transmitter units;
  - at least one streaming transmitter unit adapted to begin transmitting in a contention-window time slot assigned by the controller; and
  - at least one other transmitter unit adapted to begin transmitting in a randomly selected contention-window slot, the randomly selected contention-window slot being selected from contention-window slots other than the assigned contention-window slots, the at least one streaming transmitter unit and at least one other transmitter unit sensing the transmit medium and not beginning to transmit in a contention window if another unit has begun transmitting.
8. (Original) The wireless communication system of claim 7, wherein the indication of the available contention-window slots is an indication of the first unassigned contention-window slot.
9. (Original) The wireless communication system of claim 7 wherein the streaming data transmitted by the streaming transmitter unit comprises audio data.

10. (Original) The wireless communication system of claim 7 wherein the streaming data transmitted by the streaming transmitter unit comprises video data.
11. (Original) The wireless communication system of claim 7 wherein a limited number of assignable contention-window slots are available.
12. (Withdrawn) A wireless communication system comprising:
  - a transmitter unit wirelessly transmitting data to a dumb receiver unit;
  - the dumb receiver unit adapted to receive data from the transmitter but not adapted to send an acknowledgement signal to the transmitter unit; and
  - a surrogate unit adapted to acknowledge the reception of data for the dumb receiver unit with a surrogate acknowledgement signal to the transmitter unit.
13. (Withdrawn) The wireless communication system of claim 12 wherein there are multiple dumb receiver units for each surrogate unit.
14. (Withdrawn) The wireless communication system of claim 12 wherein the dumb receiver unit is unable to transmit data.
15. (Withdrawn) The wireless communication system of claim 12 wherein the surrogate unit is a control unit for the system.

16. (Withdrawn) The wireless communication system of claim 12 wherein the acknowledgement signal is a medium-access-control acknowledgement signal.
17. (Previously Presented) A base station for a wireless network comprising:
  - a first circuit for receiving radio frequency messages from transmitter units;
  - a second circuit for assigning slots to transmitters in contact with the base station, the second circuit operable to assign a slot to a transmitter based upon the transmitting characteristics of the transmitter;wherein the base station provides, to the transmitter units which do not fall within the transmitting characteristic, an indication of available slots aside from slots assigned to transmitters which have transmitting characteristics.
18. (Previously presented) The base station of claim 17 wherein the second circuit assigns a slot based on a low packet failure rate requirement of data transmitted by the transmitter.
19. (Previously presented) The base station of claim 17 wherein the second circuit assigns a slot based on a low latency requirement of data transmitted by the transmitter.
20. (Previously presented) The base station of claim 17 wherein the second circuit assigns a slot based on whether a transmitter is transmitting streaming data.
21. (Previously presented) The base station of claim 17 wherein the second circuit assigns a slot based on whether a transmitter is transmitting video data.

22. (Previously presented) The base station of claim 17 wherein the second circuit assigns a slot based on whether a transmitter is transmitting audio data.


If, in the opinion of the Examiner, an interview would expedite the prosecution of this application, the Examiner is invited to call the undersigned attorney at the number indicated below.

Please charge any additional required fee or credit any overpayment not otherwise paid or credited to our deposit account.

Respectfully submitted,

THELEN REID & PRIEST, LLP

Dated: 5/6/05

  
Khaled Shami  
Reg. No. 38,745

Thelen Reid & Priest LLP  
P.O. Box 640640  
San Jose, CA 95164-0640  
Tel. (408) 292-5800  
Fax. (408) 287-8040